Hammer-On Flange Clip, Bottom Mount













- Can be used to support boxes, fixtures or other applications from beam flanges
- Assorted attachment points provided to reduce inventory
- Requires only a hammer to install







Part Number	Article Number	Flange Thickness FT	Rod Size RS	Static Load 1 F1	Static Load 2 F2	Static Load 3 F3	Certifications	Standard Packaging Quantity
Material: Spring Steel – Finish: nVent CADDY Armour								
M24	-	3 – 8 mm	M6	440 N	330 N	110 N	cULus	100 pc
M58	-	8 – 14 mm	M6	440 N	330 N	110 N	cULus	100 pc
M912	-	14 – 20 mm	M6	440 N	330 N	110 N	cULus	100 pc
Material: Stainless Steel 301 (EN 1.4310)								
EM24S1	179720	3 – 8 mm	М6	200 N	110 N	200 N	-	100 pc
EM58S1	179730	8 – 14 mm	M6	200 N	110 N	200 N	-	100 pc
EM912S1	179740	14 – 20 mm	M6	200 N	110 N	200 N	-	100 pc

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent 's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent All rights reserved nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.

