



# VF-Ti/T Rod to C-Purlin Clip



- Hammer-on or install from the floor with the VAFT tool
- Provides an attachment for nVent CADDY Speed Link assemblies, wire, S-hooks, or chain from purlin and bar joist



Finish: nVent CADDY Armour

Part Number	Article Number	Hole Size HS	Hole Type	Flange Thickness FT	Height H	Static Load F	Certifications
Material: Spring Steel							
VF146T	-	9.50 mm	Plain	1.5 – 6.0 mm	132 mm	700 N	cULus
VF146TI	-	0.38"	Threaded	1.5 – 6.0 mm	132 mm	700 N	cULus
Material: Steel							
VF14T10	179060	10.00 mm	Plain	1.5 – 6.0 mm	110 mm	700 N	-

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

#### WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.erico.com](http://www.erico.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2019 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.

